


OFFER LIST



ARG 105 mobil



1385 x 13 x 0,65

	90°	+45°	+60°
●	105	70	40
■	105	65	40
■	105 x 110	65 x 85	40 x 45

Main motor	230 V, 50 Hz, 0,55 kW
Saw blade speed	55 m/min.
Machine dimensions	Dimension drawing
Machine weight	29 kg

DESCRIPTION

Small portable bandsaw designed for construction sites, installations and workshop production. In order to minimize the total weight the arm, base plate and table are made of cast aluminium. To achieve the maximum service life the vice and wheels of the saw blade are made of grey cast iron. Saw blade feed into cut, arm uplift and material clamping are carried out manually.

- Modern concept of the bandsaw arm allows for large cutting ranges in upright and angular cuts.
- Continuous adjustment of the cutting angle within the range 90°–60° when the workpiece is clamped tight.
- Simple locking and adjusting of the desired cutting angle on the angle scale.
- Maximum cutting accuracy and saw blade service life in this category of bandsaws.
- High-precision three-side hardmetal bandsaw guidance.
- Manufactured bearing of running wheels and tensioning wheel system are the same as in big professional machines.
- Professional, noiseless and maintenance-free band drive is provided by an industrial electric motor with worm gearbox.
- The machine is equipped with a 200mm workpiece stop.

All pictures shown are for illustration purpose only. Actual product may vary due to product enhancement.

PHOTOGALLERY



ACCESSORIES



DR105/130/200/235*

Workpiece stop - Standard equipment

Simple stop for setting the required length of the material to be cut.